INSTALLATION INSTRUCTIONS #1002836 INLINE PANEL-STILE STIFFENER PACKET 1080 SERIES AND #1001008 INLINE PANEL-STILE ALCOVE PACKET

Tools Necessary:

• 1/4" Drill bit

• 3/16" Drill bit

DrillT-27 Pin-in-head Torx Bit

Included Materials:


#1002836

- 1 pc 1002831 U-Channel 3/4" x 78" high
- 2 pcs 1002665 Button Head Screw 5/8"
- 2 pcs 1002666 Sex Bolt

.

- #1001008
- 3 pcs 1000282 Alcove Joggle Bracket
- 3 pcs 1000974 Y-Bracket
- 18 pcs 1002499 Torx Screw
- 6 pcs 1002495 Torx Screw 2"

- Slide 3/4" U-Channel over 3/4" thick stile so that channel is centered between headrail and shoe. Orient channel so three sets of double holes are closer to the floor.
- 2. Drill 1/4" diameter holes through Phenolic (top and bottom only). Use holes on U-Channel as a template.







4. Drill 3/16" diameter


x 7/16" holes

5. Drill 3/16" diameter x 7/16" holes (**Do not drill thru)** on 1/2" thick panel using hole pattern of Alcove Joggle Brackets (mounted to U-channel on stile) as template.






3. Use 1002665 Button Head Screws - 5/8" and 1002666 Sex Bolts in topmost and bottom-most holes to secure U-Channel Bracket to stile.



6. Use 1002499 Torx Screws - 7/16" to secure Alcove Joggle Bracket to 1/2" Thick Panel.





In the U.S.A.: BOBRICK WASHROOM EQUIPMENT, INC.

200 Commerce Drive, Clifton Park, New York 12065-1350 • Tel: (518) 877-7444 • FAX: 518-877-5029 11611 Hart Street, North Hollywood, California 91605-5882 • Tel: (818) 982-9608 • FAX: 818-503-1102 or email Bobrickcustomerservice@bobrick.com

BUILDING VALUE SINCE 1906 © 2013 by Bobrick Washroom Equipment, Inc. Form No. 1002836 r1/2/13 Printed in U.S.A.

In Canada: BOBRICK WASHROOM EQUIPMENT COMPANY 45 Rolark Drive, Scarborough, Ontario M1R 3B1 • FAX: (877) 423-8555

INSTALLATION INSTRUCTIONS #1002836 INLINE PANEL-STILE STIFFENER PACKET 1090 SERIES AND #1002670 INLINE PANEL-STILE ALCOVE PACKET

Tools Necessary:

• Drill • T-27 Pin-in-head Torx Bit


Included Materials:


#1002836

- 1 pc 1002831 U-Channel 3/4" x 78" high
- 1/4" Drill bit
- 2 pcs 1002665 Button Head Screw 5/8"
- 2 pcs 1002666 Sex Bolt


- #1002670
- 3 pcs 1000282 Alcove Joggle Bracket
- 3 pcs 1000975 F-Bracket
- 6 pcs 1002664 Button Head Screw 3/8"
- 6 pcs 1002495 Torx Screw 2"
- 6 pcs 1002499 Torx Screw
- 6 pcs 1002665 Button Head Screw 5/8"
- 12 pcs 1002666 Sex Bolt


- 1. Slide 3/4" U-Channel over 3/4" thick stile so that channel is centered between headrail and shoe. **Orient channel** so three sets of double holes are closer to the floor.
- 2. Drill 1/4" diameter holes through Solid Color Reinforced Composite (SCRC) material. Use holes on U-Channel as a template.
- 3. Use 1002665 Button Head Screws - 5/8" and 1002666 Sex Bolts in topmost and bottom-most holes to secure **U-Channel Bracket** to stile.






- 4. Use 1002665 **Button Head** Screws - 5/8" and 1002666 Sex Bolts to attach (3) 1000282 Alcove Joggle Brackets onto 3/4" U-Channel. Place Alcove Joggle Brackets on inside of toilet stall.
- 5. Drill 1/4" diameter holes through 1/2" thick panel using hole pattern of Alcove Joggle Brackets (mounted to U-channel on stile) as template.





- 6. Use 1002664 Button Head
 - Screws 3/8" and 1002666 Sex Bolts to secure Alcove Joggle Bracket to 1/2" Thick Panel.





In the U.S.A.: BOBRICK WASHROOM EQUIPMENT, INC.

200 Commerce Drive, Clifton Park, New York 12065-1350 • Tel: (518) 877-7444 • FAX: 518-877-5029 11611 Hart Street, North Hollywood, California 91605-5882 • Tel: (818) 982-9608 • FAX: 818-503-1102 or email Bobrickcustomerservice@bobrick.com

© 2013 by Bobrick Washroom Equipment, Inc. Form No. 1002837 r1/2/13 Printed in U.S.A. In Canada: BOBRICK WASHROOM EQUIPMENT COMPANY

45 Rolark Drive, Scarborough, Ontario M1R 3B1 • FAX: (877) 423-8555