

MODEL ZW209BP - Pressure Reducing Valve with Low Flow By-Pass Control Valve Order Form



Customer: _____ Date: _____
 Contact: _____ Email: _____
 Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
 Contact Customer Care for details on return policies.

Size: (Check one) DN32 DN40 DN50 DN65 DN80 DN100 DN150
 (Reduced Port Only)

Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control
 - "O" Option * - Opening Speed Control (Standard on DN100 or smaller)


Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body
 - "R" Option - Reduced Port Body (DN80 - DN150 Flanged only)

End Connections (Check one) Size Range (DN40 - DN150)

Options	Description	Options	Description
<input type="checkbox"/> Standard	- ANSI Class 150 Flanges	<input type="checkbox"/> "PN6"	- ISO Class PN6 Flanges
<input type="checkbox"/> "BSD"	- BS10/AS2129 Table D Flanges	<input type="checkbox"/> "PN10"	- ISO Class PN10 Flanges
<input type="checkbox"/> "BSE"	- BS10/AS2129 Table E Flanges	<input type="checkbox"/> "PN16"	- ISO Class PN16 Flanges
<input type="checkbox"/> "BSF"*	- BS10/AS2129 Table F Flanges	<input type="checkbox"/> "PN25"*	- ISO Class PN25 Flanges
<input type="checkbox"/> "BSH"*	- BS10/AS2129 Table H Flanges	Size Range (DN32 - DN80)	
<input type="checkbox"/> "G"	- IPS Grooved, ANSI/AWWA C 606	<input type="checkbox"/> "TH"	- NPT Threaded, ANSI/ASME B1.20.1
<input type="checkbox"/> "BG"	- Grooved DN65 (76.1mm pipe OD)	<input type="checkbox"/> "BS"	- Threaded British Pipe Parallel BSPP/G size ISO
<input type="checkbox"/> "Y"*	- ANSI Class 300 Flanges (DN40 - DN100)	<input type="checkbox"/> "BT"	- Threaded British Pipe Tapered BSPT/Rc size ISO



Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 - "V" Option * - Viton Rubber Internals, Rated 82°C (only available with "LP" or "HP" options)
 - "Z" Option * - Visual Position Indicator

Pilot Options:

- Check one
- Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer
 - Standard - PRXL Pilot (15 - 150 psi)
 - "LP" Option * - PV-PRD Pilot (35 - 170 kPa)
 - "HP" Option * - PV-PRD Pilot (205 - 2050 psi)
-
- Check all that apply
- Standard - Copper Tubing and Brass Fittings
 - "ST" Option * - Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing")
 - "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing. "GL" Option included)
 - "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)
-
- Check all that apply
- "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option * - Liquid Filled Pressure Gauge

*Adder to standard price applies

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

