## MODEL ZW209BP - Pressure Reducing Valve with Low Flow By-Pass



## **Control Valve Order Form**

| Custo  | me  | r:   | Date:   |
|--|-----|--|---|
| Contact:   |     |  | Email:  |
| Telephone/Fax:   |     |  | Ref. P. O   |
| _  |     | red Valve In   | All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.   |
| Quantity:  |     |  |   |
| Function Options: Valve body is ductile iron, epoxy coated   |     |  |   |
| Check one  End C  Check one  Main V  Check all that apply  | Opi | "C" Option * - "L" Option * - "O" Option * - tions:  Standard - "A" Option - "R" Option - nections: Standard - "G" Option - "TH" Option - "Y" Option * - Options: Standard - "V" Option * - "Z" Option * - | Check Valve with Isolation Valve Closing Speed Control Opening Speed Control (Standard on 4" or smaller)  Full Port Globe Body Angle Style Body Reduced Port Body (3" - 6" Flanged only)  ANSI Class 150 Flanges (1-1/2" - 6") IPS Grooved (1-1/2" - 4") NPT Threaded (1-1/4" - 3") ANSI Class 300 Flanges (1-1/2" - 6")  Stainless Steel Seat, Seal Ring Retainer and Stem Guide Viton Rubber Internals, Rated 180°F (only available with"LP" or "HP" options) Visual Position Indicator |
| Pilot Options:  Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer |     |  |   |
| Check<br>one   |     | Standard - "LP" Option * -   | PRXL Pilot (15 - 150 psi) PV-PRD Pilot (5 - 25 psi) PV-PRD Pilot (30 - 300 psi)   |
| Check<br>all that<br>apply   |     | Standard - "ST" Option * - "SP" Option * -   | Copper Tubing and Brass Fittings Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing") All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing. "GL" Option included) Stainless Steel Braided Hoses (only replaces Copper Tubing)   |
| Check<br>all that<br>apply   |     | "RV" Option - "GL" Option * -  | Pilot Installed on Reverse Side Liquid Filled Gauge   |

\*Adder to standard price applies

1747 Commerce Way Paso Robles, CA 93446 Phone: 855-663-9876 Fax: 805-237-7197 Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

