

MODEL ZW209H - Pressure Reducing and Pressure Sustaining Valve



Control Valve Order Form

Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10" 12" 14" 16"

Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control
 - "O" Option * - Opening Speed Control (Standard on 4" or smaller)

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (1-1/4" - 10")
 - "R" Option - Reduced Port Body (3" - 10" Flanged only)



End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (1-1/2" - 16")
 - "G" Option - IPS Grooved (1-1/2" - 10")
 - "TH" Option - NPT Threaded (1-1/4" - 3")
 - "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 16")

Main Valve Options:

- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
- Optional "Z" Option * - Visual Position Indicator

Pilot Options:

MUST CHECK ONE REDUCING BOX & ONE SUSTAINING PRESSURE RANGE BOX

		SUSTAINING→					
		LP3 5 - 15 psi	LP2 10 - 35 psi	LP 30 - 90 psi	S 50 - 200 psi	HP 150 - 300 psi	
↓ REDUCING	LP*	5 - 25 psi	LPLP3	LPLP2	LPLP	LPS	LPHP
	S	15 - 150 psi	SLP3	SLP2	SLP	(no adder)	SHP
	HP*	30 - 300 psi	HPLP3	HPLP2	HPLP	HPS	HPHP

- Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer
- Standard - Copper Tubing and Brass Fittings
- Check all that apply
 - "ST" Option * - Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing")
 - "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)
 - "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)
- Check all that apply
 - "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option * - Liquid Filled Pressure Gauge

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

