

# Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer: \_\_\_\_\_ Date: \_\_\_\_\_

Contact: \_\_\_\_\_ Email: \_\_\_\_\_

Telephone/Fax: \_\_\_\_\_ Ref. P. O. \_\_\_\_\_

## Required Valve Information

Quantity: \_\_\_\_\_

Size:  2" (DN50)  2-1/2" (DN65)  3" (DN80)  4" (DN100)  6" (DN150)  8" (DN200)  10" (DN250)  
(Check one)

### Body Options:

Check one  Standard - Full Port Globe Body  
 "A" Option - Angle Style Body

**Valve body is ductile iron, epoxy coated**

### End Connections (Check one)


Size Range 2" - 10" (DN50 - DN250)

Options	Description
<input type="checkbox"/> Standard	ANSI Class 150 Flanges
<input type="checkbox"/> "BSD"	BS10/AS2129 Table D Flanges
<input type="checkbox"/> "BSE"	BS10/AS2129 Table E Flanges
<input type="checkbox"/> "BSF"*	BS10/AS2129 Table F Flanges
<input type="checkbox"/> "BSH"*	BS10/AS2129 Table H Flanges
<input type="checkbox"/> "G"	IPS Grooved, ANSI/AWWA C 606
<input type="checkbox"/> "BG"	Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD)
<input type="checkbox"/> "Y"*	ANSI Class 300 Flanges

Options	Description
<input type="checkbox"/> "PN6"	ISO Class PN6 Flanges
<input type="checkbox"/> "PN10"	ISO Class PN10 Flanges
<input type="checkbox"/> "PN16"	ISO Class PN16 Flanges
<input type="checkbox"/> "PN25"*	ISO Class PN25 Flanges

Size Range (2" - 3", DN50 - DN80)

<input type="checkbox"/> "TH"	NPT Threaded, ANSI/ASME B1.20.1
<input type="checkbox"/> "BS"	Threaded British Pipe Parallel BSPP/G size ISO
<input type="checkbox"/> "BT"	Threaded British Pipe Tapered BSPT/Rc size ISO



### Main Valve Options:

Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide  
Optional  "Z" Option \* - Visual Position Indicator

### Pilot Options:

Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge (UL), and "Wye" Type Strainer

Check one	<input type="checkbox"/> Standard	- PV-RLF Pilot (50 - 200 psi) (340 - 1380kPa)
	<input type="checkbox"/> "HP" Option *	- PV-RLF Pilot (150 - 300 psi) (1000 - 2050kPa)
Check one	<input type="checkbox"/> Standard	- Copper Tubing and Brass Fittings
	<input type="checkbox"/> "ST" Option *	- Stainless Steel Tubing (included with SP option, only replaces Copper Tubing)
	<input type="checkbox"/> "SP" Option *	- All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)
Optional	<input type="checkbox"/> "RV" Option	- Pilot on Reverse Side



**UL & ULC Listed, FM® Approved**

\*Adder to standard price applies

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

