

# MODEL ZW204 - Non-Modulating Float Valve Control Valve Order Form



Customer: \_\_\_\_\_ Date: \_\_\_\_\_

Contact: \_\_\_\_\_ Email: \_\_\_\_\_

Telephone/Fax: \_\_\_\_\_ Ref. P. O. \_\_\_\_\_

## Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee.  
Contact Customer Care for details on return policies.

Size: (Check one) ☐ 1-1/4" ☐ 1-1/2" ☐ 2" ☐ 2-1/2" ☐ 3" ☐ 4" ☐ 6" ☐ 8" ☐ 10" ☐ 12" ☐ 14" ☐ 16"

## Function Options:

- Check all that apply
- |                                       |   |
|---------------------------------------|---|
| <input type="checkbox"/> "C" Option * | - Check Valve with Isolation Valve                  |
| <input type="checkbox"/> "L" Option * | - Closing Speed Control (Standard on 8" and larger) |
| <input type="checkbox"/> "O" Option * | - Opening Speed Control                             |

Valve body is ductile iron, epoxy coated

## Body Options:

- Check one
- |                                     |   |
|-------------------------------------|---|
| <input type="checkbox"/> Standard   | - Full Port Globe Body                      |
| <input type="checkbox"/> "A" Option | - Angle Style Body (1-1/4" - 10")           |
| <input type="checkbox"/> "R" Option | - Reduced Port Body (3" - 10" Flanged only) |

## End Connections:

- Check one
- |                                       |   |
|---------------------------------------|---|
| <input type="checkbox"/> Standard     | - ANSI Class 150 Flanges (1-1/2" - 16") |
| <input type="checkbox"/> "G" Option   | - IPS Grooved (1-1/2" - 10")            |
| <input type="checkbox"/> "TH" Option  | - NPT Threaded (1-1/4" - 3")            |
| <input type="checkbox"/> "Y" Option * | - ANSI Class 300 Flanges (1-1/2" - 16") |

## Main Valve Options:

- Check all that apply
- |  |   |
|--|---|
| <input checked="" type="checkbox"/> Standard | - Stainless Steel Seat, Seal Ring Retainer and Stem Guide |
| <input type="checkbox"/> "V" Option *        | - Viton Rubber Internals, Rated 180°F (1-1/4" - 6")       |
| <input type="checkbox"/> "Z" Option *        | - Visual Position Indicator                               |

## Pilot Options:

- Check all that apply
- |  |   |
|--|---|
| <input checked="" type="checkbox"/> Standard | - Isolation Valves, and "Wye" Type Strainer   |
| <input type="checkbox"/> Standard            | - Copper Tubing and Brass Fittings  |
| <input type="checkbox"/> "ST" Option *       | - Stainless Steel Tubing (replaces Copper Tubing, with "VM" Option only)                          |
| <input type="checkbox"/> "SP" Option *       | - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included) |
| <input type="checkbox"/> "SH" Option *       | - Stainless Steel Braided Hoses (replaces Copper Tubing, with "VM" Option only)                   |

- Must check one
- |  |                             |
|--|-----------------------------|
| <input type="checkbox"/> Standard      | - Remotely Mounted Float    |
| <input type="checkbox"/> "VM" Option * | - Valve Mounted Float Pilot |

SEE IMAGES

- Check one
- |  |   |
|--|---|
| <input type="checkbox"/> Standard      | - 2' Standard Float Rod (Stainless Steel Rod & Float) |
| <input type="checkbox"/> "R1" Option * | - 1' Float Rod Extension (3' total length)            |
| <input type="checkbox"/> "R2" Option * | - 2' Float Rod Extension (4' total length)            |
| <input type="checkbox"/> "R3" Option * | - 3' Float Rod Extension (5' total length)            |

Optional ☐ "RV" Option - Pilot Installed on Reverse Side

\*Adder to standard price applies



DIRECTION OF FLOW ⇒  
STANDARD - REMOTELY MOUNTED  
FLOAT



DIRECTION OF FLOW ⇒  
("VM" OPTION)

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com



Document#  
OF-ZW204

Rev. E  
Date: 4/16