

Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Size: (Check one) DN50 DN65 DN80 DN100 DN150 DN200 DN250

Body Options:

- Check one Standard - Full Port Globe Body
 "A" Option - Angle Style Body


Valve body is ductile iron, epoxy coated

End Connections (Check one)

- | Options | Description |
|-----------------------------------|---|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges |
| <input type="checkbox"/> "BSD" | - BS10/AS2129 Table D Flanges |
| <input type="checkbox"/> "BSE" | - BS10/AS2129 Table E Flanges |
| <input type="checkbox"/> "BSF"* | - BS10/AS2129 Table F Flanges |
| <input type="checkbox"/> "BSH"* | - BS10/AS2129 Table H Flanges |
| <input type="checkbox"/> "G" | - IPS Grooved, ANSI/AWWA C 606 |
| <input type="checkbox"/> "BG" | - Grooved DN65, or DN150 (76.1 mm or 165.1mm pipe OD) |
| <input type="checkbox"/> "Y"* | - ANSI Class 300 Flanges |

Size Range (DN50 - DN250)

- | Options | Description |
|----------------------------------|--------------------------|
| <input type="checkbox"/> "PN6" | - ISO Class PN6 Flanges |
| <input type="checkbox"/> "PN10" | - ISO Class PN10 Flanges |
| <input type="checkbox"/> "PN16" | - ISO Class PN16 Flanges |
| <input type="checkbox"/> "PN25"* | - ISO Class PN25 Flanges |



Size Range (DN50 - DN80)

- | | |
|-------------------------------|--|
| <input type="checkbox"/> "TH" | - NPT Threaded, ANSI/ASME B1.20.1 |
| <input type="checkbox"/> "BS" | - Threaded British Pipe Parallel BSPP/G size ISO |
| <input type="checkbox"/> "BT" | - Threaded British Pipe Tapered BSPT/Rc size ISO |

Main Valve Options:

- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 Optional "Z" Option * - Visual Position Indicator

Pilot Options:

- Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge (UL), and "Wye" Type Strainer

- | | | |
|-----------|--|--|
| Check one | <input type="checkbox"/> Standard | - PV-RLF Pilot (340 - 1380kPa) |
| | <input type="checkbox"/> "HP" Option * | - PV-RLF Pilot (1000 - 2050kPa) |
| Check one | <input type="checkbox"/> Standard | - Copper Tubing and Brass Fittings |
| | <input type="checkbox"/> "ST" Option * | - Stainless Steel Tubing (included with SP option, only replaces Copper Tubing) |
| | <input type="checkbox"/> "SP" Option * | - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing) |
| Optional | <input type="checkbox"/> "RV" Option | - Pilot on Reverse Side |



UL & ULC Listed, FM® Approved

*Adder to standard price applies

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

