

# MODEL ZW209 - Pressure Reducing Valve Control Valve Order Form



Customer: \_\_\_\_\_ Date: \_\_\_\_\_

Contact: \_\_\_\_\_ Email: \_\_\_\_\_

Telephone/Fax: \_\_\_\_\_ Ref. P. O. \_\_\_\_\_

## Required Valve Information

Quantity: \_\_\_\_\_


All returns are subject to a restocking/refurbishing fee.  
Contact Customer Care for details on return policies.

Size: (Check one)  DN32     DN40     DN50     DN65     DN80     DN100  
 DN150     DN200     DN250     DN300     DN350     DN400

### Function Options:

- Check all that apply
- "C" Option \* - Check Valve with Isolation Valve
  - "L" Option \* - Closing Speed Control
  - "O" Option \* - Opening Speed Control (Standard on DN100 or smaller)

**Valve body is ductile iron, epoxy coated**



### Body Options:

- Check one
- Standard - Full Port Globe Body
  - "A" Option - Angle Style Body (DN32 - DN250)
  - "R" Option - Reduced Port Body (DN80 - DN250 Flanged Only)

### End Connections (Check one) Size Range (DN40 - DN400)

- | Options                           | Description   | Options                          | Description              |
|-----------------------------------|---|----------------------------------|--------------------------|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges                              | <input type="checkbox"/> "PN6"   | - ISO Class PN6 Flanges  |
| <input type="checkbox"/> "BSD"    | - BS10/AS2129 Table D Flanges                         | <input type="checkbox"/> "PN10"  | - ISO Class PN10 Flanges |
| <input type="checkbox"/> "BSE"    | - BS10/AS2129 Table E Flanges                         | <input type="checkbox"/> "PN16"  | - ISO Class PN16 Flanges |
| <input type="checkbox"/> "BSF"*   | - BS10/AS2129 Table F Flanges                         | <input type="checkbox"/> "PN25"* | - ISO Class PN25 Flanges |
| <input type="checkbox"/> "BSH"*   | - BS10/AS2129 Table H Flanges                         |                                  |                          |
| <input type="checkbox"/> "G"      | - IPS Grooved, ANSI/AWWA C 606                        |                                  |                          |
| <input type="checkbox"/> "BG"     | - Grooved DN65, or DN150 (76.1 mm or 165.1mm pipe OD) |                                  |                          |
| <input type="checkbox"/> "Y"*     | - ANSI Class 300 Flanges                              |                                  |                          |

### Size Range (DN32 - DN80)

- "TH" - NPT Threaded, ANSI/ASME B1.20.1
- "BS" - Threaded British Pipe Parallel BSPP/G size ISO
- "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

### Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
  - "V" Option \* - Viton Rubber Internals, Rated 82°C (DN32 - DN150 only available with "LP" or "HP" Option)
  - "Z" Option \* - Visual Position Indicator

### Pilot Options:

- Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer

- Check one
- Standard - PRXL Pilot (100 - 1000kPa)
  - "LP" Option \* - PV-PRD Pilot (35 - 170kPa)
  - "HP" Option \* - PV-PRD Pilot (205 - 2050kPa)

- Check all that apply
- Standard - Copper Tubing and Brass Fittings
  - "ST" Option \* - Stainless Steel Tubing ("included with SP option, only replaces Copper Tubing")
  - "SP" Option \* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve and Copper Tubing. "GL" Option included)
  - "SH" Option \* - Stainless Steel Braided Hoses (only replaces Copper Tubing)

- Check all that apply
- "RV" Option - Pilot Installed on Reverse Side
  - "GL" Option \* - Liquid Filled Pressure Gauge

\*Adder to standard price applies

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurnwilkins.com  
or visit us online at www.zurn.com

