

MODEL ZW204E - Non-Modulating Float Valve with Solenoid Control Valve Order Form



Customer: _____

Date: _____

Contact: _____

Email: _____

Telephone/Fax: _____

Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) ☐ 1-1/4" ☐ 1-1/2" ☐ 2" ☐ 2-1/2" ☐ 3" ☐ 4" ☐ 6" ☐ 8" ☐ 10" ☐ 12" ☐ 14" ☐ 16"

Function Options:

- Check all that apply
- ☐ "C" Option * - Check Valve with Isolation Valve
 - ☐ "L" Option * - Closing Speed Control (Standard on 8" and larger)
 - ☐ "O" Option * - Opening Speed Control

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- ☐ Standard - Full Port Globe Body
 - ☐ "A" Option - Angle Style Body (1-1/4" - 10")
 - ☐ "R" Option - Reduced Port Body (3" - 10" Flanged only)

End Connections:

- Check one
- ☐ Standard - ANSI Class 150 Flanges (1-1/2" - 16")
 - ☐ "G" Option - IPS Grooved (1-1/2" - 10")
 - ☐ "TH" Option - NPT Threaded (1-1/4" - 3")
 - ☐ "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 16")

Main Valve Options:

- Check all that apply
- ☒ Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
 - ☐ "V" Option * - Viton Rubber Internals, Rated 180°F (1-1/4" - 6")
 - ☐ "Z" Option * - Visual Position Indicator

Pilot Options:

- Check all that apply
- ☒ Standard - Isolation Valves, and "Wye" Type Strainer
 - ☐ Standard - Copper Tubing and Brass Fittings
 - ☐ "ST" Option * - Stainless Steel Tubing (replaces Copper Tubing, with "VM" Option only)
 - ☐ "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
 - ☐ "SH" Option * - Stainless Steel Braided Hoses (replaces Copper Tubing, with "VM" Option only)
- Must check one**
- ☐ Standard - Remotely Mounted Float
 - ☐ "VM" Option * - Valve Mounted Float Pilot

- Check one
- ☐ Standard - 2' Standard Float Rod (Stainless Steel Rod & Float)
 - ☐ "R1" Option * - 1' Float Rod Extension (3' total length)
 - ☐ "R2" Option * - 2' Float Rod Extension (4' total length)
 - ☐ "R3" Option * - 3' Float Rod Extension (5' total length)

- Must check one**
- ☐ "NC" Option - Normally Closed (energize to open) Main Valve, 120vac/60 Hz Solenoid
 - ☐ "NO" Option - Normally Open (energize to close) Main Valve, 120vac/60 Hz Solenoid
 - ☐ "24NC" Option - Normally Closed (energize to open) Main Valve, 24vac/60 Hz Solenoid
 - ☐ "24NO" Option - Normally Open (energize to close) Main Valve, 24vac/60 Hz Solenoid
 - ☐ "NS" Option * - Non-Standard Solenoid (specify Voltage/Frequency/AC/DC/Operation)
V _____ Hz _____ AC/DC _____ NO/NC _____

- Optional
- ☐ "MO" Option * - Manual Operator on Solenoid Valve (to control during power failure)
 - ☐ "RV" Option - Pilot Installed on Reverse Side

*Adder to standard price applies



DIRECTION OF FLOW ⇒
**STANDARD -
REMOTELY MOUNTED
FLOAT**



DIRECTION OF FLOW ⇒
("VM" OPTION)

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

