



**MATERIALS:**

**Cover** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel. All-welded construction. Exposed surfaces have satin finish. Equipped with an adjustable bracket to hold cups, a refill-indicator slot, and a tumbler lock. Secured to mounting plate with a full-length stainless steel piano-hinge.

**Mounting Plate** — 18-8 S, type-304, 22-gauge (0.8mm) stainless steel.

Available in Stainless Steel only!

**OPERATION:**

Cups pull down out of unit. To load, unlock with key provided and swing cover down. Unit holds 150 3-oz (0.1-L) paper or plastic flat-bottom cups. Bracket inside cover adjusts to hold up to 6-oz (0.2-L) cups. Slot on front indicates refill time.

**INSTALLATION:**

Mount unit on wall with four #8 x 1-1/4" (4.2 x 32mm) sheet-metal screws (not furnished) at points indicated by an S. For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws, or provide 1/8" (3mm) toggle bolts or expansion bolts. If unit projects above top of wainscot, provide aluminum channel or other filler to eliminate gap between mounting plate and finish face of wall.

**SPECIFICATION:**

Surface-mounted paper cup dispenser shall be type-304 stainless steel with all welded construction; exposed surfaces shall have satin finish. Cover of unit shall be secured to mounting plate with a full-length stainless steel piano-hinge and equipped with a refill-indicator slot and a tumbler lock. Unit shall be adjustable to dispense 3- to 6-oz (0.1- to 0.2-L) paper or plastic flat-bottom cups.

**Surface-Mounted Paper Cup Dispenser shall be Model CD-1 of Gamco Commercial Restroom Accessories, A Division of Bobrick, Durant, OK.**