



**CONSTRUCTION:**

Fabricated of type 304 heavy gauge stainless steel. All welded construction with exposed surfaces having a #4 satin-finish. One piece seamless 22-gauge (0.8mm) flange provided with 1/4" (6mm) return for rigidity. EXTRA HEAVY 18-gauge (1.2mm) doors, warp-free, hung on continuous stainless steel piano-hinge, and fitted with tumbler locks. All welded construction. 700 C-fold, 900 Multi-fold, or 1200 single-fold towels. Waste receptacle is 24-gauge (0.6mm) with 7.5-gallon (28.4-L) capacity.

**OVERALL DIMENSIONS:**

14" W x 58" H x 6" D (356 x 1473 x 152mm)

**INSTALLATION:**

Provide framed wall opening. Recessed depth required from finish face of wall is 5-3/4" (145mm) deep. Check plans and coordinate with mechanical engineers to avoid protrusion from opposite wall, pipes, conduits, electrical wires, etc. If installing in plaster wall, recommend grounding. If installing where unit projects above top of wainscot, provide filler to prevent gap from finished wall and flange of unit. If installing in block walls, use metal expansion shields. 1/8" (3mm) gap recommended between units for door clearance.

**ADA GUIDE:**

Access to paper towels should be 15" to 48" (381 to 1219mm) above the finish floor to allow forward and side reach by people in wheelchairs. Units should not project more than 4" (102mm) from the wall.

**Recessed Towel Dispenser and Waste Receptacle Combination shall be Model TW-6 of GAMCO Commercial Restroom Accessories, A Division of Bobrick, One Gamco Place, Durant, OK.**